


TAN.FPS.2250-30 Datasheet

2250 Litre Triple Skinned
Bunded Steel Tank
c/w 30min Integral
Fireproofing



Capacity	2250 Litre
Length	2070mm
Width	1460mm
Height*	1430mm
Weight	720kg

Tank:

A triple skinned bunded tank, the inner tank provides the required storage area, the second tank forms the required bund with capacity for 110% of the total liquid being stored & the third tank provides the housing for the integral fire barrier. The tank is suitable for storage of Diesel, Kerosene & certain other oils. Please check before usage.

This Tank Complies With:

Oil Pollution Prevention Guidelines
(England & Wales) 2002 PPG2. BS799 pt5.

Dimensions:

Outer tank dimensions:

(L) 2070mm x (W) 1460mm x (H) 1430mm*

* For the overall height of this tank, allow an additional 115mm (50mm for the base bearers and 65mm for the top box).

Weight:

720kg

Recommended Base Size:

(L) 2670mm x (W) 2060mm

Specification

- ✓ Tough Steel construction
- ✓ 2250 litres (495 galls) capacity
- ✓ 30 min integral fireproof barrier (non absorbent)
- ✓ 1 No. 2" top socket for fill point
- ✓ 2 No. 1 1/2" top socket (for tank & bund)
- ✓ 1 No. 2" tank to bund vent
- ✓ 1 No. 2" bund vent
- ✓ 1 No. 1" bottom outlet socket
- ✓ 1 No. 1" top suction drain socket (plugged)
- ✓ Tank contents gauge (Spiral Float Gauge)
- ✓ Outlet filter kit (optional extra)
- ✓ Mounted on 100mm x 50mm high channel support bearers
- ✓ 10 year warranty



10 Year Tank
Warranty



High Quality
British-Made
Tanks



ISO 9001
Quality
Assurance