


TAN.FPS.1050-60 Datasheet

1050 Litre Triple Skinned
Bunded Steel Tank
c/w 60min Integral
Fireproofing



Capacity	1050 Litre
Length	2110mm
Width	890mm
Height*	1470mm
Weight	570kg

Tank:

A triple skinned bunded tank, the inner tank provides the required storage area, the second tank forms the required bund with capacity for 110% of the total liquid being stored & the third tank provides the housing for the integral fire barrier. The tank is suitable for storage of Diesel, Kerosene & certain other oils. Please check before usage.

This Tank Complies With:

Oil Pollution Prevention Guidelines
(England & Wales) 2002 PPG2. BS799 pt5.

Dimensions:

Outer tank dimensions:

(L) 2110mm x (W) 890mm x (H) 1470mm*

* For the overall height of this tank, allow an additional 115mm (50mm for the base bearers and 65mm for the top box).

Weight:

570kg

Recommended Base Size:

(L) 2710mm x (W) 1490mm

Specification

- ✓ Tough Steel construction
- ✓ 1050 litres (230 galls) capacity
- ✓ 60 min integral fireproof barrier (non absorbent)
- ✓ 1 No. 2" top socket for fill point
- ✓ 2 No. 1 1/2" top socket (for tank & bund)
- ✓ 1 No. 2" tank to bund vent
- ✓ 1 No. 2" bund vent
- ✓ 1 No. 1" bottom outlet socket
- ✓ 1 No. 1" top suction drain socket (plugged)
- ✓ Tank contents gauge (Spiral Float Gauge)
- ✓ Outlet filter kit (optional extra)
- ✓ Mounted on 100mm x 50mm high channel support bearers
- ✓ 10 year warranty



10 Year Tank
Warranty



High Quality
British-Made
Tanks



ISO 9001
Quality
Assurance